


## Higo - Motor - Z1115A

### Male cable connector

Z1115AG P 00 DU 1000

<https://www.higoconnector.com/de/e-bike-steckverbinder/z1115agp00du1000>



## Spezifikationen

### General Characteristics

|                    |                                    |
|--------------------|------------------------------------|
| Number of contacts | 11 (3+8)                           |
| Connector shape    | Plug                               |
| Gender             | Male                               |
| Color              | Black                              |
| Upper temperature  | 80 °C                              |
| Lower temperature  | -25 °C                             |
| IP Protection      | IP67                               |
| Mating cycles      | 200 Times                          |
| Connector diameter | 15 mm                              |
| Fitting length     | 70 mm                              |
| Cable Length       | 1000 mm                            |
| Cable diameter     | 7.5 mm                             |
| Wire section       | 3 x 2,5 + 8 x 0,14 mm²             |
| Remark             | Other cable length/type on request |

# Produktdatenblatt

## Higo - Motor - Z1115A

### Male cable connector

### Electrical Parameters

|                            |                           |
|----------------------------|---------------------------|
| Rated current              | 25 / 2 A                  |
| Rated voltage              | 48 V AC / 60 V DC         |
| Max. insulation resistance | $\geq 20 \text{ M}\Omega$ |
| Max. contact resistance    | $\leq 10 \text{ m}\Omega$ |

### Material

|                     |                  |
|---------------------|------------------|
| Material jacket     | PVC              |
| Insulation wire     | PTFE             |
| Material of contact | Copper Alloy     |
| Contact plating     | Gold over Nickel |