

New Delta power supply series for a wide range of industrial applications



LYTE II SERIES



FORCE GT SERIES



PMT2 SERIES



SOLUTIONS
CONNECTOR - POWER SUPPLY - ASSEMBLY

INDUSTRIAL
POWER SUPPLIES



DELTA FORCE GT SERIES

NEW



Ultimate performance, efficiency and reliability



Ultra-compact design



Cold start at -40 °C



Conformal coating on PCBAs to protect against common dust and pollutants



Built-in constant current circuit for reactive loads



Model name	Phase	Output Voltage (Vdc)	Output Current (A)	Output Power (W)	Input Voltage range (Vac)	Dimensions (L x W x H mm)
DRF-12V120W1GBA	1	12	10	120	90-264	124 x 30 x 116,8
DRF-24V120W1GBA	1	24	5	120	90-264	124 x 30 x 116,8
DRF-48V120W1GBA	1	48	2,5	120	90-264	124 x 30 x 116,8
DRF-12V240W1GBA	1	12	20	240	90-264	124 x 40 x 116,8
DRF-24V240W1GBA	1	24	10	240	90-264	124 x 40 x 116,8
DRF-48V240W1GBA	1	48	5	240	90-264	124 x 40 x 116,8
DRF-24V480W1GBA	1	24	20	480	90-264	124 x 56 x 116,8
DRF-48V480W1GBA	1	48	10	480	90-264	124 x 56 x 116,8
DRF-24V120W3GBA	2-3	24	5	120	3 x 320-575 (3-Phase) or 2 x 340-575 (2-Phase)	124 x 40 x 116,8
DRF-24V240W3GBA	2-3	24	10	240	3 x 320-575 (3-Phase) or 2 x 340-575 (2-Phase)	124 x 50 x 125,3
DRF-24V480W3GBA	2-3	24	20	480	3 x 320-575 (3-Phase) or 2 x 340-575 (2-Phase)	124 x 65 x 127,3
DRF-24V960W3GBA	2-3	24	40	960	3 x 320-575 (3-Phase) or 2 x 340-575 (2-Phase)	124 x 110 x 128,7

DELTA



Complete output voltage range 12V, 24V, 48V



Universal AC input voltage range



<0,3W No load power consumption



Compact design and high power density



Complies with IEC 60950-1, IEC/EN/UL 62368-1, IEC/EN 61010 & IEC/EN 61010-2-201 and SEMI F47 certification. Also meets DOE VI standards for high power efficiency.

Model name	Phase	Output Voltage (Vdc)	Output Current (A)	Output Power (W)	Input Voltage range (Vac)	Dimensions (L x W x H mm)
DRL-12V75W1AZ	1	12	6,25	75	85-264	123,6 x 27 x 102
DRL-24V75W1AZ	1	24	3,125	75	85-264	123,6 x 27 x 102
DRL-48V75W1AZ	1	48	1,57	75	85-264	123,6 x 27 x 102
DRL-12V120W1EN	1	12	10	120	90-264	123,6 x 30 x 117,2
DRL-24V120W1EN	1	24	5	120	90-264	123,6 x 30 x 117,2
DRL-48V120W1EN	1	48	2,5	120	90-264	123,6 x 30 x 117,2
DRL-12V240W1EN	1	12	20	240	90-264	123,6 x 40 x 117,2
DRL-24V240W1EN	1	24	10	240	90-264	123,6 x 40 x 117,2
DRL-48V240W1EN	1	48	5	240	90-264	123,6 x 40 x 117,2
DRL-24V480W1AX	1	24	20	480	85-264	123,6 x 85,5 x 128,5

DELTA PMT2 SERIES



Household appliance approvals: IEC/EN60335-1, IEC/EN 61558-1, IEC/EN 61558-2-16



No load power consumption



Overtoltage category III



Universal AC input voltage range



Cold start at -40°C



Low-profile design (height: 30 mm)



Meantime between failure > 700.000 hours

Model name	Phase	Output Voltage (Vdc)	Output Power (W)	Input Voltage range (Vac)	Dimensions (L x W x H mm)
PMT-**V35W2BA	1	12, 15, 24, 30, 36, 48	35	90-264	99 x 82 x 29
PMT-**V50W2BA	1	12, 15, 24, 30, 36, 48	50	90-264	99 x 82 x 29
PMT-**V75W2BA	1	12, 15, 24, 30, 36, 48	75	90-264	99 x 97 x 30
PMT-D1V75W2XA	1	5, 12	75	90-264	129 x 97 x 30
PMT-D2V75W2XA	1	5, 24	75	90-264	129 x 97 x 30
PMT-**V100W2BA	1	12, 15, 24, 30, 36, 48	100	90-264	129 x 97 x 30
PMT-**V150W2BA	1	12, 15, 24, 30, 36, 48	150	90-132, 180-264 (Selectable by Switch)	159 x 97 x 30
PMT-**V150W2CA	1	12, 15, 24, 30, 36, 48	150	90-264	159 x 97 x 30
PMT-**V200W2BX	1	12, 24, 36, 48	200	90-132, 180-264 (Selectable by Switch)	159 x 97 x 30
PMT-**V350W2BX	1	12, 24, 36, 48	350	90-132, 180-264 (Selectable by Switch)	215 x 115 x 30



Our mission

'We relieve our customers by advising, customizing and stocking the right connector and/or power supply solution'



The right solution



Tailored to your needs



Delivered at the right time



Slachthuisstraat 68 bus 6, B-2300 Turnhout
+32 (0)14 73 53 70 - sales@ac-solutions.be
www.ac-solutions.be

