

# Product data sheet

## Higo - Signal - Micro A

### Micro A male plug connector

## Push-on (no locking)

Z205AG P 00 DS 3000

<https://www.higoconnector.com/en/e-bike-connector/z205agp00ds3000>



## Specifications

### General Characteristics

<b>Number of contacts</b>	2
<b>Connector shape</b>	Plug
<b>Gender</b>	Male
<b>Color</b>	Black
<b>Upper temperature</b>	80 °C
<b>Lower temperature</b>	-25 °C
<b>Locking</b>	Push-on (no locking)
<b>IP Protection</b>	IP67
<b>Mating cycles</b>	200 Times
<b>Connector diameter</b>	4,8 mm
<b>Fitting length</b>	35,4 mm
<b>Cable Length</b>	3000 mm
<b>Cable diameter</b>	2,4 mm

# Product data sheet

## Higo - Signal - Micro A

### Micro A male plug connector

<b>Wire section</b>	2 x 0,14 mm <sup>2</sup>
<b>Remark</b>	Other cable length/type on request

# Product data sheet

## Higo - Signal - Micro A

### Micro A male plug connector

#### Electrical Parameters

<b>Rated current</b>	2 A
<b>Rated voltage</b>	48 V AC / 60 V DC
<b>Max. insulation resistance</b>	$\geq 20$ M $\Omega$
<b>Max. contact resistance</b>	$\leq 10$ m $\Omega$

#### Material

<b>Material jacket</b>	PVC
<b>Insulation wire</b>	FEP
<b>Material of contact</b>	Copper Alloy
<b>Contact plating</b>	Gold over Nickel